STAND ALONE POWER **BATTERY AC 100K3-100**



Globe Power's lithium ion Battery AC units provide a reduction of diesel consumption and zero emission assisting in reducing carbon footprint and hitting green energy emission targets.

Suitable for a high load start up and low running power demands, the stand-alone power system is both efficient in power usage and cost.













PRODUCT SPECIFICATIONS GENERAL

Model Voltage Output Power Frequency Solar Input

BAC 100k3-100
400v AC 3 phase
100kVA continous, 250kVA peak
50Hz
2 x 15kWp (max) 500V (max)
Remote start feature

BATTERY

Generator

Battery Voltage AC Output Capacity Recharge Time

Lithium Iron Phosphate 650V DC 92kWh 3 hours (10-100%)

OPERATIONAL DATA

Operating Temperature	0°C - 50°C (derates above 35°C)
Altitude	0 - 1500m (>1500m derating)
IP Rating	IP54
Input	Hardwire terminals
	• 63A 3ph plug - IP66
Output	Hardwire terminals
	• 1 x 125A 3ph Outlets
	• 1 x 63A 3ph Outlets
	• 2 x 3ph 32A Outlets
	• 2 x 15A Outlets
	• 2 x 15A Outlets - IP66

UNIT INFORMATION

Dimensions (HxWxD) Weight

2200 x 2200 x 1100 1,950kg

GLOBEPOWER.NET