

KEY FEATURES

Globe Power's Sunflare GP-110K-H Solar Lighting Tower has been built to suit various industries and is compliant with metropolitan and mining specifications.

- 7 day timer
- Day/night modes
- Jack pads
- Dimmer
- Fire extinguisher
- Emergency stop
- Isolators
- AC charger
- Wheel chocks
- Tie down points
- Lifting points
- Backup HATZ DC generator



- USER-FRIENDLY OPERATION INTERFACE
- SOLAR & ADVANCED LITHIUM ION BATTERY
- PORTABLE & EASY TO TRANSPORT
- AUSTRALIAN DESIGNED & ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

| | |
|--------------|---------------------------------|
| Model | Sunflare - GP110k-H |
| Lumen Output | 110,000 |
| Mast Height | 9 metres |
| Mast Type | Hydraulic/Cable |
| Lights | 4 x 250w LED Modules (Dimmable) |
| Coverage | 19.200m ² @ 5 lux |

OPERATIONAL DATA

| | |
|---------------------|------------|
| Wind Rating | 100km/h |
| Working Temperature | 0 to 50°C |
| Light Bar Tilt | 0 to 90° |
| Light Bar Rotation | 355° |
| Stabiliser Supports | 4 x Manual |

BATTERY

| | |
|------------------|----------------------------------|
| Battery | 15.4kWh |
| Run Time | 27 hours (Battery only) |
| Solar | 1.8kWp |
| Solar Tilt | 30° |
| Solar Efficiency | 1 hour of sun/2.5 hours of light |

UNIT INFORMATION

| | |
|------------------------|---|
| Dimensions (Transport) | 3660 x 2240 x 2930 (LxWxH) |
| Dimensions (Deployed) | 3600 x 4370 x 9700 (LxWxH) |
| Weight | 1,990kg |
| Security | Wheel/hitch locks, wheel clamp, security wheel nuts |

