



KEY FEATURES

Globe Power's Eco GP56K Solar Lighting Tower has been built to suit various industries and is compliant with metropolitan and mining specifications.

- 7 day timer
- Day/night modes
- Fire extinguisher
- Emergency stop
- Battery isolators
- Adjustable solar tilt
- AC charger
- Wheel chocks
- Tie down points
- Lifting points



PRODUCT SPECIFICATIONS

GENERAL

Model	Eco GP56K
Lumen Output	56,000
Mast Height	7.5 metres
Mast Type	Hydraulic/Cable
Lights	2 x 200w LED Modules (Dimmable)
Coverage	110m x 100m at 5 lux

OPERATIONAL DATA

Wind Rating	100km/h
Working Temperature	0 to 50°C
Light Bar Tilt	0 to 90° Electric
Light Bar Rotation	355° Electric
Stabiliser Supports	4 x Manual

BATTERY

Battery	10.8kWh AGM
Run Time	30 hours
Solar	1.23kWp
Solar Tilt	30° to 45°
Solar Efficiency	1 hr of sun/3 hrs of light

UNIT INFORMATION

Dimensions (Towing)	3140 x 1500 x 2900 (LxWxH)
Dimensions (Stowed)	2200 x 3455 x 7650 (LxWxH)
Dimensions (Deployed)	2200 x 1500 x 2900m (LxWxH)
Weight	1,450kg
Trailer Type	Single Axle
Security	Wheel/hitch locks, wheel clamp, folding drawbar, security wheel nuts

