



-  AUSTRALIAN DESIGNED
-  FUEL EFFICIENT
-  CUSTOMISABLE
-  DURABLE

Powered by



## PRODUCT SPECIFICATIONS

### GENERAL

Model	GP350C
Power Type	Diesel
Prime Power (kW/kVA)	250/313
Standby Power (kW/kVA)	280/350
Rated Current	434 AMPS
Operating Ambient Temp.	50°C

### ENGINE

Engine Model	Cummins MTAA11-G3
Aspiration	Turbo-charged and air to air aftercooled
No. of Cylinders	6
Governor Type	Electronic Governor
Lubricating Oil Capacity	36.7L

### ALTERNATOR

Model	GP314E
Frequency	50/60
Rate Power (kW/kVA)	260/325
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±0.5%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

### UNIT

Dimensions (LxWxH)	4200 x 1500 x 2400
Dry Weight	4450 kg

### FUEL CONSUMPTION

Fuel Consumption*	70.1 (L/h)
Fuel Tank Capacity	1220L

### NOISE LEVEL

Sound Pressure at 7m/dB 74

### SAFETY FEATURES

ISO Compliant  
Outlet package with AS3000 compliant RCD protection  
Emergency E Stop

### CONTROL SYSTEM

Operator friendly DSE control system

### ENCLOSURE FEATURES

Sound attenuated canopies  
Powder coated finish  
IP65 rating  
Fully bunded extended run fuel tanks

### WARRANTY

12 months warranty, further options available

### OPTIONS

3 way fuel valves  
Multiple synchronisation of units  
Load share capabilities

\*Fuel consumption based on 75% load