



Globe Power Mobile AC units are industrial grade power banks, which utilise a range of different power sources (solar, grid, genset, battery input) to provide portable AC power. Quick installation will result in a permanent power solution with a 10 year battery life, that is low maintenance, and provides exceptional return on investment.

Globe Power's use of the best components can all be remotely monitored to see power consumption and battery life.



Powered by



PRODUCT SPECIFICATIONS

GENERAL

Model	MAC10K-20
Voltage	230V AC
Output Power	10kVA continuous load, 22.5kVA peak
Frequency	50Hz

BATTERY

Battery Type	Lithium Iron Phosphate
Battery Voltage	51.2V DC
AC Output Capacity	16.7kWh
Recharge Time	3 hours (25-100%)
Monitoring	5" Touchscreen, Remote cloud monitoring

OPERATIONAL DATA

Operating Temperature	0°C - 50°C
Altitude	0 - 1500m (>1500m derating)
IP Rating	IP54
Input	1 x 32A Inlet - IP66
Output	2 x 15A - Outlets IP66

INPUTS

Solar Input	4kWp max. 250v max.
Generator/Grid	Remote Start feature, 7.4kVA input

UNIT

Dimensions (HxWxD)	1320 x 920 x 1060
Weight	450kg