



Globe Power Mobile AC units are industrial grade power banks, which utilise a range of different power sources (solar, grid, genset, battery input) to provide portable AC power. Quick installation will result in a permanent power solution with a 10 year battery life, that is low maintenance, and provides exceptional return on investment.

Globe Power's use of the best components can all be remotely monitored to see power consumption and battery life.



Powered by



## PRODUCT SPECIFICATIONS

### GENERAL

Model	MAC 10K2-20
Voltage	240v AC Input, 120V/240 AC Output
Output Power	8kW continuous load, 18kW peak
Frequency	60Hz

### BATTERY

Battery Type	Lithium Iron Phosphate
Battery Voltage	51.2V DC
AC Output Capacity	16.7kWh
Recharge Time	3 hours (10-100%)
Monitoring	5" Touchscreen, Remote cloud monitoring

### OPERATIONAL DATA

Operating Temperature	32°F - 122°F
Altitude	0 - 4921ft (>4921ft derating)
IP Rating	NEMA 3S
Input	1 x 240v 50A Inlet - NEMA 4 1 x 120v/240v 50A Outlet - NEMA 4 2 x 20A GFCL Outlets

### INPUTS

Solar Input	8kWp max. 250v max.
Generator/Grid	Remote Start feature, 12kW input

### UNIT

Dimensions (HxWxD)	52" x 36" x 42"
Weight	990 lbs