







-  AUSTRALIAN DESIGNED
-  FUEL EFFICIENT
-  CUSTOMISABLE
-  DURABLE

Powered by



PRODUCT SPECIFICATIONS

GENERAL

Model	GP17FW-3
Power Type	Diesel
Prime Power (kW/kVA)	12/15
Standby Power (kW/kVA)	13.2/16.5
Rated Current	20AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	FAWDE 4DW81-23D
Aspiration	Turbo-Charged
No. of Cylinders	4
Governor Type	Electronic governor
Lubricating Oil Capacity	7.8L

ALTERNATOR

Model	SLG164D
Frequency	50Hz
Rate Power (kW/kVA)	112.8/16
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AVR
Voltage Regulation	±1.0%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	2000 x 1100 x 1290
Dry Weight	890 kg

FUEL CONSUMPTION

Fuel Consumption*	4.95(L/h)
Fuel Tank Capacity	160L

NOISE LEVEL

Sound Pressure at 7m/dB 75

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating
Fully bunded extended run fuel tanks

WARRANTY

12 months warranty, further options available

*Fuel consumption based on 75% load