



- AUSTRALIAN DESIGNED
- FUEL EFFICIENT
- CUSTOMISABLE
- DURABLE

Powered by
Kubota

PRODUCT SPECIFICATIONS

GENERAL

Model	GP10KLR3
Power Type	Diesel
Prime Power (kW/kVA)	8/10
Standby Power (kW/kVA)	8.8/11
Rated Current	13.9AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Kubota D722
Aspiration	Natural
No. of Cylinders	3
Governor Type	Mechanical Governor
Lubricating Oil Capacity	3.8L

ALTERNATOR

Model	Stamford GP042D
Frequency	50
Rate Power (kW/kVA)	10
Power Factor	0.8
Exciter Type	Brushless
Voltage Regulator	AS440
Voltage Regulation	1.0%
No. of Phases	3
Insulation	Class H
Protection	GP23
Altitude	1000m

UNIT

Dimensions (LxWxH)	1705 x 816 x 1168
Dry Weight	388kg

FUEL CONSUMPTION

Fuel Consumption*	2.3(L/h)
Fuel Tank Capacity	60L

NOISE LEVEL

Sound Pressure at 7m/dB 71

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE6020 control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating - Outlets 1x32 Amp 3Φ 2x15 Amp 1Φ
Fully bunded extended run fuel tanks

WARRANTY

12 months warranty or 1200 hours, as per warranty T+C.

OPTIONS

3 way fuel valves
Remote Monitoring

*Fuel consumption based on 75% load

GP-GP10KLR3-V2.2-0225