



- AUSTRALIAN DESIGNED
- FUEL EFFICIENT
- CUSTOMISABLE
- DURABLE

Powered by
Kubota

PRODUCT SPECIFICATIONS

GENERAL

Model	GP12K
Power Type	Diesel
Prime Power (kW/kVA)	9/11
Standby Power (kW/kVA)	9.9/12.1
Rated Current	15.6AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Kubota V1505-E2BG
Aspiration	Natural
No. of Cylinders	4
Governor Type	All speed mechanical governor
Lubricating Oil Capacity	6.7L

ALTERNATOR

Model	GP164C1
Frequency	50
Rate Power (kW/kVA)	10.8/13.5
Power Factor	0.8
Exciter Type	Self-excited, brushless
Voltage Regulator	AS440
Voltage Regulation	±0.5%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	1800 x 900 x 1430
Dry Weight	880kg

FUEL CONSUMPTION

Fuel Consumption*	2.4(L/h)
Fuel Tank Capacity	75L

NOISE LEVEL

Sound Pressure at 7m/dB	64
-------------------------	----

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating - Outlets 3x15 Amp 1x32 Amp 3Φ
Fully bunded extended run fuel tanks

WARRANTY

12 months warranty or 1200 Hours, as per warranty T+C.

OPTIONS

Remote Monitoring

*Fuel consumption based on 75% load