



PRODUCT SPECIFICATIONS

GENERAL

Model	GP240-30RL-LB
Rating Voltage/Frequency	AC single phase 240V/50Hz 240V/50Hz
Max Load Power	Resistive load: 30kW Inductive load: 25kVA
Load Step	Resistive load: 6 steps, 1, 2, 2, 5, 10, 10kW Inductive load: 6 steps, 1, 2, 2, 5, 5, 10kvar
PF (Power Factor)	0.8
Load Tolerance overall	±3%
Display Precision	0.5 class
Control Power	AC single phase 240V/50Hz
Wire Connection	Load power supply input --- Connector-bar
Communication Interface	RS485, RS232
Insulation	F
Cooling	Forced air cooling Horizontal inlet air Vertical cooling



OPERATING ENVIRONMENT

Ambient Temperature	-10°C~+50°C
Relative Humidity	≤95%
Altitude	≤2500m
Atmospheric Pressure	86~106kPa
Aeration Distance	3-5m no obstacle from the air inlet, more than 3m no obstacle from the air outlet

UNIT

Dimensions (LxWxH)	825 x 720 x 1350mm
Dry Weight	
Paint Colour	Grey (RAL7035)
Transportation	Hoisting via lifting lugs in top of casing

COMPONENT BRANDS

Contractor	Schneider
------------	-----------