

KEY FEATURES

Globe Power's GP65K Urban Solar Lighting Tower has been built to suit various industries and is compliant with both metropolitan and mining specifications.

- 7 day timer
- Day/night modes
- Jack pads
- Fire extinguisher
- Emergency stop
- Isolators
- Tilt sensor
- AC charger
- Wheel chocks
- Tie down points
- Lifting points



- USER-FRIENDLY
OPERATION INTERFACE
- SOLAR
- PORTABLE & EASY TO
TRANSPORT
- AUSTRALIAN DESIGNED
& ENGINEERED

PRODUCT SPECIFICATIONS

GENERAL

Model	GP65K Urban
Lumen Output	65,000
Mast Height	9 metres
Mast Type	Hydraulic/Cable
Lights	4 x 150w LED Modules (Dimmable)
Coverage	11,335m ² at 5 lux

OPERATIONAL DATA

Wind Rating	100km/h
Working Temperature	0 to 50°C
Light Bar Tilt	0 to 90° Electric
Light Bar Rotation	355° Electric
Stabiliser Supports	4 x Manual

BATTERY

Battery	14.4kWh Deep Cycle Gel
Run Time	48 hours
Solar	1.8kWp
Solar Tilt	30°
Solar Efficiency	1 hr of sun/3.5 hrs of light

UNIT INFORMATION

Dimensions (Transport)	3660 x 2240 x 2930 (LxWxH)
Dimensions (Deployed)	3600 x 4370 x 9700 (LxWxH)
Weight	1,900kg
Security	Wheel/hitch locks, wheel clamp, security wheel nuts

