



Powered by  
**Kubota**

## PRODUCT SPECIFICATIONS

### GENERAL

Model	GP10KLR3
Power Type	Diesel
Prime Power (kW/kVA)	8/10
Standby Power (kW/kVA)	8.8/11
Rated Current	13.9AMPS
Operating Ambient Temp.	50°C

### ENGINE

Engine Model	Kubota D722
Aspiration	Natural
No. of Cylinders	3
Governor Type	Mechanical Governor
Lubricating Oil Capacity	3.8L

### ALTERNATOR

Model	Stamford GP042D
Frequency	50
Rate Power (kW/kVA)	10
Power Factor	0.8
Exciter Type	Brushless
Voltage Regulator	AS440
Voltage Regulation	1.0%
No. of Phases	3
Insulation	Class H
Protection	GP23
Altitude	1000m

### UNIT

Dimensions (LxWxH)	1705 x 816 x 1168
Dry Weight	388kg

### FUEL CONSUMPTION

Fuel Consumption*	2.3(L/h)
Fuel Tank Capacity	60L

### NOISE LEVEL

Sound Pressure at 7m/dB	71
-------------------------	----

### SAFETY FEATURES

ISO Compliant  
Outlet package with AS3000 compliant RCD protection  
Emergency E Stop

### CONTROL SYSTEM

Operator friendly DSE6020 control system

### ENCLOSURE FEATURES

Sound attenuated canopies  
Powder coated finish  
IP65 rating - Outlets 1x32 Amp 3Φ 2x15 Amp 1Φ  
Fully bunded extended run fuel tanks

### WARRANTY

12 months or 1200 Hours, subject to Ts & Cs

### OPTIONS

3 way fuel valves  
Remote Monitoring

\*Fuel consumption based on 75% load

GP-GP10KLR3-V3-0625