







-  AUSTRALIAN  
DESIGNED
-  FUEL EFFICIENT
-  CUSTOMISABLE
-  DURABLE

Powered by  
**Kubota**

## PRODUCT SPECIFICATIONS

### GENERAL

Model	GP30K
Power Type	Diesel
Prime Power (kW/kVA)	20/25
Standby Power (kW/kVA)	22/28
Rated Current	35AMPS
Operating Ambient Temp.	50°C

### ENGINE

Engine Model	Kubota V3300-E2BG2
Aspiration	Natural
No. of Cylinders	4
Governor Type	Mechanical Governor
Lubricating Oil Capacity	13.2L

### ALTERNATOR

Model	SLG184F1
Frequency	50
Rate Power (kW/kVA)	22/27.5
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±1.0%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

### UNIT

Dimensions (LxWxH)	2300 x 1000 x 1570
Dry Weight	1290 kg

### FUEL CONSUMPTION

Fuel Consumption*	7.6(L/h)
Fuel Tank Capacity	210L

### NOISE LEVEL

Sound Pressure at 7m/dB	70
-------------------------	----

### SAFETY FEATURES

ISO Compliant  
Outlet package with AS3000 compliant RCD protection  
Emergency E Stop

### CONTROL SYSTEM

Operator friendly DSE control system

### ENCLOSURE FEATURES

Sound attenuated canopies  
Powder coated finish  
IP65 rating- Outlets 2x15 Amp 1Φ, 2x32 Amp 3Φ  
Fully bunded extended run fuel tanks

### WARRANTY

12 months or 1200 Hours, subject to Ts & Cs

### OPTIONS

Remote Monitoring

\*Fuel consumption based on 75% load

GP-GP30K-V3-0625