











Powered by



PRODUCT SPECIFICATIONS

GENERAL

Model GP33DZS-1
Power Type Diesel
Prime Power (kW/kVA) 30/30
Standby Power (kW/kVA) 33/33
Rated Current 125AMPS
Operating Ambient Temp. 50°C
Voltage Output 240V

ENGINE

Engine Model Deutz BFM3-T **Aspiration** Natural

Aspiration Natura
No. of Cylinders 4

Governor Type Mechanical governor

Lubricating Oil Capacity 7.5L

ALTERNATOR

ModelGP184J1Frequency50Rate Power (kW/kVA)24/24Power Factor1

Exciter Type Self-excited

Voltage Regulator AS440

Voltage Regulation ±0.5%

No. of Phases 1

InsulationClass HProtectionIP21Altitude1000m

UNIT

Dimensions (LxWxH) 2240 x 1000 x 1380

Dry Weight 1400kg

FUEL CONSUMPTION

Fuel Consumption ★ 5.8(L/h)
Fuel Tank Capacity 160L

NOISE LEVEL

Sound Pressure at 7m/dB 64

SAFETY FEATURES

AS300 Compliant Emergency E Stop Fitted with ATS Remote stop start option

CONTROL SYSTEM

Operator friendly DSE6120 control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish

Fully bunded 3 way external fuel connections

WARRANTY

12 months warranty, subject to Ts & Cs

OPTIONS

Remote Monitoring

*Fuel consumption based on 75% load

GP-GP33DZS-1 V1-042