



 AUSTRALIAN
DESIGNED

 FUEL EFFICIENT

 CUSTOMISABLE

 DURABLE

Powered by



PRODUCT SPECIFICATIONS

GENERAL

Model	GP275C
Power Type	Diesel
Prime Power (kW/kVA)	200/250
Standby Power (kW/kVA)	220/275
Rated Current	347.8 AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Cummins 6LTAA8.9-G2
Aspiration	Turbo-charged and air to air aftercooled
No. of Cylinders	6
Governor Type	Electronic governor
Lubricating Oil Capacity	27.6L

ALTERNATOR

Model	GP274K1
Frequency	50/60
Rate Power (kW/kVA)	200/250
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±1.0%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	4200 x 1500 x 2400
Dry Weight	4760 kg

FUEL CONSUMPTION

Fuel Consumption*	39 (L/h)
Fuel Tank Capacity	1220L

NOISE LEVEL

Sound Pressure at 7m/dB	75
-------------------------	----

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating - Outlets 2x15 Amp 1Φ 2x32 Amp 3Φ 1x63 Amp 3Φ
Fully bunded extended run fuel tanks

WARRANTY

12 months or 1200 Hours, subject to Ts & Cs

OPTIONS - ALL STANDARD

3 way fuel valves
Multiple synchronisation of units
Load share capabilities

*Fuel consumption based on 75% load

GP-GP275C-V4-1125