

STORM SERIES



- AUSTRALIAN DESIGNED
- FUEL EFFICIENT
- CUSTOMISABLE
- DURABLE

Powered by
Kubota

PRODUCT SPECIFICATIONS

GENERAL

Model	GPS30K
Power Type	Diesel
Prime Power (kW/kVA)	22/27.5
Standby Power (kW/kVA)	24/30
Rated Current	38AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Kubota V3300-E2BG2
Aspiration	Natural
No. of Cylinders	4
Governor Type	Mechanical Governor
Lubricating Oil Capacity	13.2L

ALTERNATOR

Model	SLG184F1
Frequency	50
Rate Power (kW/kVA)	22/27.5
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±0.50%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	2300 x 1000 x 1430
Dry Weight	1250 kg

FUEL CONSUMPTION

Fuel Consumption*	7.6(L/h)
Fuel Tank Capacity	160L

NOISE LEVEL

Sound Pressure at 7m/dB 64

STANDARD FEATURES

- 50°C rated radiator
- Powder coated finish
- All moving parts fitted with safety guards
- Emergency E stop
- 24hr Bunded Fuel Tank
- Outlets 1 x 3PH 32amp
- Outlets 2 x 1PH 15amp
- Rated Lifting Lugs
- 4P ABB MCB

CONTROL SYSTEM

Operator friendly DSE control system

WARRANTY

12 months or 1200 Hours, subject to Ts & Cs

OPTIONS

Remote Monitoring

*Fuel consumption based on 75% load

GP-GPS30K-V1-0626